



memory space located outside processor or m

[Search Patents](#)[Advanced Patent Search](#)  
[Google Patent Search Help](#)Try uppercase "OR" to search for either of two terms. [\[details\]](#)

Patents Showing:  View as:  Patents 1 - 10 on memory space located outside proces:  
[Sort by relevance](#) | [Sort by date \(new first\)](#) | [Sort by date \(old first\)](#)

### Information exchange processor

US Pat. 4418382 - Filed May 6, 1980 - Allied Corporation

The lower half as previ- microprocessor is to service, and establishes the micro  
- ously explained is called processor memory space, and processor as either ...

### Management system for the memory of a processor or microprocessor

US Pat. 4602328 - Filed Dec 17, 1982 - L'Etat Francais represente par le Ministre des P.T.T. (Centre National d'Etudes des  
Telecommunications), Institut National de Recherche en Informatique et en Automatique

In particular, it makes it possible to separate the located between the  
processor and the physical memory space reserved for input - output operations  
and ...

### Digital data processor with high reliability

US Pat. 4654857 - Filed Aug 2, 1985 - Stratus Computer, Inc.

The local address is a selected section of the virtual memory space and is ...  
fault signals which originate outside the processor and are communicated to ...

### Microprocessor based computer with virtual memory space in overwritable memory

US Pat. 5511206 - Filed Feb 25, 1994 - Sony Corporation

1 that a data base A and a data base B are stored in the outside memory 3, ...  
invention to provide a microprocessor controlled processor whereby the user ...

### Method for automatically transitioning from V86 mode to protected mode in a ...

US Pat. 5255379 - Filed Dec 28, 1990 - Sun Microsystems, Inc.

The use of virtual addresses allows addressing of memory space in addition to  
... the processor operates essentially as a fast 8088 or 8086 microprocessor.  
...

### High resolution ECG waveform processor

US Pat. 4630204 - Filed Feb 21, 1984 - Mortara Instrument Inc.

Once the processor 304 starts DRAM, PROM, or I/O that the microprocessor 304 is  
to ... The acknowl- 35 area in the memory space a particular memory device ...

### Central processing apparatus for fault-tolerant computing

US Pat. 4453215 - Filed Oct 1, 1981 - Stratus Computer, Inc.

Each microprocessor applies two inputs to the multiplexor 104, ... Page Fault I  
signal when a user addresses a location outside the allocated memory space. ...

### Multiprocessor system featuring global data multiplation

US Pat. 4928224 - Filed May 19, 1988 - Bull HN Information Systems Italia S.p.A.

It must be noted that although main memory physical space, ... than "0000" or "  
0001," an external storage resource; that is, a resource outside processor 1.  
...

### Subscriber terminal with plug in expansion card

US Pat. 5367571 - Filed Dec 2, 1992 - Scientific-Atlanta, Inc.

Further, the microprocessor 128 reads an input port line PAO to tell memory  
space of these pages may be internal (located whether the expansion card 138 is  
...



Result Page:    [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#)    [Next](#)

[Google Patent Search Help](#) | [Advanced Patent Search](#)

[Google Home](#) - [About Google](#) - [About Google Patent Search](#)

©2009 Google